

Fiber Launch Cable

Features

- Low Insertion Loss
- High Repeatability
- Compact Size

Applications

- OTDR Test
- Telecommunication

Specifications

Parameters	Unit	Values
Connector Type		FC,SC,ST, LC
Operating wavelength	nm	1310/1550/1625
Insertion Loss	150~1000m	≤0.25
	1500~2000m	≤0.50
Return Loss	APC	≥60
	UPC	≥50
Repeatability	dB	≤0.1
Fiber Type	dB	SMF-28e; OM2; OM3; OM4, MMF62.5
Package Size	Ring Type for 150~1000m	101x16
	Box Type for 1500~2000m	190x140x38
Operating Temperature	°C	0 ~ +85

Photo



Ordering Information

JP- ①①-②②-③③③③-④④④④④-⑤-⑥⑥⑥-⑦

①	Connector 1	FA=FC/APC; FC=FC/UPC; SA=SC/APC; SC=SC/UPC; ST=ST/UPC; XX=Others;
②	Connector 2	FA=FC/APC; FC=FC/UPC; SA=SC/APC; SC=SC/UPC; ST=ST/UPC; XX=Others;
③	Test Wavelength	1310; 1550; 1625;
④	Pigtail Type	3000C=3mm loose tube;
⑤	Fiber Type	1=SMF-28e; OM2; OM3; OM4; 3=MMF 62.5/125;
⑥	Fiber Length	150=150m; 500=500m; 1km; 1.5km; 2km; XX=Others;
⑦	Package	R=Ring Type; B=Box Type;